



HOYT
WIRE CLOTH

PO Box 4647 Lancaster, PA 17604
(717) 394-6871 Fax: (717) 394-1640
www.hoytwirecloth.com

The *Shape*
of things to come™

SERPA XLT ALTERNATING WIRE SPECS CURRENTLY AVAILABLE

SERPA XLT AW AUTOMATICALLY RECEIVES POLYURETHANE UNLESS OTHERWISE SPECIFIED

AVAILABLE IN PROD CODE:

- 84 Supertough Serpa XLT Alternating Wires
- 85 Stainless Steel Serpa XLT Alternating Wires
- 86 Supertough Serpa XLT Alternating Wires with Poly
- 87 Stainless Steel Serpa XLT Alternating Wires with Poly

OPENING	MM	WIRE DIA	AW
5/32"	4	0.072(.053/.079)	0.054(.036/.060)
7/32"	5.5	.080(.063/.084)	.072(.053/.076)
9/32"	7.1	.120(.092/.135)	.092(.072/.100)
5/16"	7.9	0.120(.092/.135)	0.092(.072/.100)
3/8"	9.5	0.120(.092/.135)	0.092(.072/.100)
3/8"	9.5	0.148(.120/.161)	0.120(.092/.135)
7/16"	11.1	0.148(.120/.161)	0.120(.092/.135)
15/32"	12	0.148(.120/.161)	0.120(.092/.135)
1/2"	12.7	0.162(.121/.186)	0.135(.101/.152)
9/16"	14.3	0.162(.121/.186)	0.135(.101/.152)
9/16"	14.3	.177(.121/.205)	.148(.118/.161)
5/8"	16	0.162(.121/.186)	0.135(.101/.152)
11/16"	17.5	0.162(.121/.186)	0.135(.101/.152)
3/4"	19.1	0.225(.162/.263)	0.192(.145/.204)
7/8"	22.2	0.250(.175/.291)	0.207(.160/.230)
15/16"	23.8	0.250(.175/.291)	0.207(.160/.230)
1"	25.4	.225(.162/.263)	.192(.120/.215)
1"	25.4	0.250(.175/.291)	0.207(.160/.230)
1 1/8"	28.6	0.250(.175/.291)	0.207(.160/.230)