



HOYT
WIRE CLOTH

PO Box 4647 Lancaster, PA 17604
(717) 394-6871 Fax: (717) 394-1640
www.hoytwirecloth.com

The **Shape**
of things to come™

SERPA SPECS CURRENTLY AVAILABLE

SERPA AUTOMATICALLY RECEIVES POLYURETHANE UNLESS OTHERWISE SPECIFIED

CODE: 18 SUPERTOUGH SERPA WITH POLY
19 STAINLESS STEEL SERPA WITH POLY

*NO-FILL

| OPENING IN INCHES | OPENING IN MM | WIRE DIA | O. A % |
|-------------------|---------------|----------|--------|
| 33/64" | 13 | 0.148 | 56.6% |
| 5/64" | 2 | 0.047 | 43.2% |
| 3/32" | 2.4 | 0.047 | 44.9 |
| 3/32" | 2.4 | 0.063 | 43.3% |
| 7/64" | 2.8 | 0.047 | 49.1% |
| 7/64" | 2.8 | 0.054 | 45.0% |
| 1/8" | 3.2 | 0.047 | 52.8% |
| 1/8" | 3.2 | 0.054 | 48.8% |
| 1/8" | 3.2 | 0.063 | 44.2% |
| 1/8" | 3.2 | 0.072 | 44.1% |
| 17/128" | 3.3 | 0.063 | 45.5% |
| 5/32" | 4 | 0.047 | 51.5% |
| 5/32" | 4 | 0.054 | 55.2% |
| 5/32" | 4 | 0.063 | 50.7% |
| 5/32" | 4 | 0.072 | 46.8% |
| 3/16" | 4.7 | 0.054 | 60.2% |
| 3/16" | 4.7 | 0.072 | 52.1% |
| 3/16" | 4.7 | 0.080 | 49.1% |
| 3/16" | 4.7 | 0.092 | 45.9% |
| 7/32" | 5.5 | 0.072 | 52.4% |
| 7/32" | 5.5 | 0.092 | 49.3% |
| 1/4" | 6.4 | 0.054 | 57.9% |
| 1/4" | 6.4 | 0.080 | 57.4% |
| 1/4" | 6.4 | 0.092 | 53.4% |
| 1/4" | 6.4 | 0.105 | 48.4% |
| 9/32" | 7.1 | 0.092 | 52.1% |
| 5/16" | 7.9 | 0.072 | 66.0% |
| 5/16" | 7.9 | 0.080 | 63.3% |
| 5/16" | 7.9 | 0.092 | 59.6% |
| 5/16" | 7.9 | 0.105 | 56.0% |
| 5/16" | 7.9 | 0.120 | 51.5% |
| 5/16" | 7.9 | 0.135 | 49.5% |
| 5/16" | 7.9 | 0.162 | 46.7% |
| 11/32" | 8.7 | 0.120 | 53.0% |
| 11/32" | 8.7 | 0.135 | 50.5% |
| 3/8" | 9.5 | 0.105 | 61.0% |
| 3/8" | 9.5 | 0.120 | 57.4% |
| 3/8" | 9.5 | 0.135 | 52.4% |
| 3/8" | 9.5 | 0.162 | 49.2% |
| 25/64" | 10 | 0.105 | 57.2% |
| 25/64" | 10 | 0.120 | 55.7% |
| 25/64" | 10 | 0.162 | 49.8% |
| 13/32" | 10.3 | 0.105 | 62.3% |
| 7/16" | 11.1 | 0.105 | 65.0% |
| 7/16" | 11.1 | 0.120 | 61.6% |
| 7/16" | 11.1 | 0.135 | 58.4% |
| 7/16" | 11.1 | 0.148 | 53.5% |
| 15/32" | 11.9 | 0.162 | 53.8% |
| 1/2" | 12.7 | 0.080 | 64.5% |
| 1/2" | 12.7 | 0.120 | 65.0% |
| 1/2" | 12.7 | 0.135 | 62.0% |
| 1/2" | 12.7 | 0.148 | 56.4% |
| 1/2" | 12.7 | 0.162 | 55.6% |
| 1/2" | 12.7 | 0.192 | 53.5% |
| 17/32" | 13.5 | 0.120 | 60.6% |

| OPENING IN INCHES | OPENING IN MM | WIRE DIA | O. A % |
|-------------------|---------------|----------|--------|
| 17/32" | 13.5 | 0.192 | 53.0% |
| 9/16" | 14.3 | 0.135 | 65.0% |
| 9/16" | 14.3 | 0.148 | 62.7% |
| 9/16" | 14.3 | 0.162 | 57.6% |
| 19/32" | 15 | 0.192 | 54.8% |
| 5/8" | 16 | 0.135 | 61.0% |
| 5/8" | 16 | 0.148 | 65.4% |
| 5/8" | 16 | 0.162 | 59.3% |
| 5/8" | 16 | 0.177 | 57.1% |
| 5/8" | 16 | 0.192 | 56.3% |
| 11/16" | 17.5 | 0.120 | 63.1% |
| 11/16" | 17.5 | 0.148 | 67.7% |
| 11/16" | 17.5 | 0.162 | 65.5% |
| 3/4" | 19.1 | 0.148 | 63.2% |
| 3/4" | 19.1 | 0.162 | 67.6% |
| 3/4" | 19.1 | 0.192 | 63.4% |
| 3/4" | 19.1 | 0.225 | 57.6% |
| 13/16" | 20.6 | 0.192 | 60.5% |
| 7/8" | 22.2 | 0.177 | 58.5% |
| 7/8" | 22.2 | 0.192 | 67.2% |
| 7/8" | 22.2 | 0.250 | 59.6% |
| 15/16" | 23.8 | 0.192 | 68.9% |
| 1" | 25.4 | 0.192 | 70.4% |
| 1" | 25.4 | 0.207 | 58.5% |
| 1" | 25.4 | 0.225 | 66.6% |
| 1 1/16" | 27 | 0.177 | 65.3% |
| 1 1/16" | 27 | 0.250 | 57.4% |
| 1 1/8" | 28.6 | 0.207 | 61.3% |
| 1 1/4" | 31.8 | 0.192 | 65.4% |
| 1 1/4" | 31.8 | 0.250 | 60.2% |
| * 1 1/2" | 38.1 | 0.250 | 69.0% |
| 2" | 50.8 | 0.250 | 73.50% |

